

## DFWLKI 3GD

"DFWLKI3GD": MULTIFUNCTION WEIGHT INDICATOR FOR ATEX 2 & 22 ZONES



Easy to programme and use, versatile and high performing weight indicator, with IP68 stainless steel case. Ideal for using in areas classified as hazardous with protection methods according to  
II 3G Ex nR IIC T6 Gc X  
II 3D Ex tc IIIC T130°C Dc IP68 X.  
CE-M approvable (OIML R-76/EN 45501).

Working in cooperation with:

**Vetek AB**

Hantverksvägen 15 - 76493 Väddö, Sweden  
Tel +46176208920 info@vetek.com

The best solution  
for advanced industrial  
applications

## MAIN FEATURES:

- Waterproof 17-key numeric-functional keypad.
- LCD 25mm backlit display with 6 high contrast digits and icons for indication of active functions.
- Waterproof IP68 STAINLESS STEEL case, with sealed rubber gasket, easy to clean and resistant in harsh and corrosive environments.
- Dimensions in mm: 243x145x78,4 mm.
- Suitable for use on the table, column, or wall.
- A/D 24 bit converter, 4 channels, up to 200 conv./sec. autoselect and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3  $\mu$ V/d in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with built-in resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and set-up from keypad or from PC with DINITOOLS.
- Power supply:
  - DFWLKI3GD: through 110-240Vac internal power adapter;
  - DFWLKI3GDB: through optional external battery (BP6ESTATEX3GD code), rechargeable in safe area.

## MAIN CERTIFICATIONS

- EC Type Approval (EN45501)
- OIML R76

## FUNCTIONS:

- KEYBOARD:
  - Zeroing, Automatic tare, Presetable tare, printing and/or data transmission, selectable function command, on/off switching, database of 10 tares, 2 numeric IDs, keyboard lock, repetition of last printout made.
- SELECTABLE FUNCTIONS:
  - High Resolution Weighing x 10.
  - Net/Gross or lb/kg conversion.
  - Accumulation.
  - Formula weighing.
  - +/- Checkweighing.
  - Percentage weighing.
  - Approved transmission of the weight to PC/PLC (with Alibi memory ALMEM option).
  - Counting (Max. resolution of 1.500.000 divisions).
  - In/Out Truck weighing.
  - Hold and Peak.

## I/O SECTION

- RS232/C bidirectional port for connection to PC in safe zone.
- RS232/C bidirectional port for connection to printer or labeller in safe zone.

## OPTIONS (only available at time of order)

- Real time clock.
- Alibi memory with real time clock.



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
Nogent-sur-Marne

DINI ARGEO  
GMBH  
Sinsheim - Germany

DINI ARGEO  
UK Ltd  
Taunton - United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
Shanghai - China

DINI ARGEO  
WEIGHBRIDGES  
Calto (RO) – Italy



HEAD OFFICE  
Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena - Italy



### ***Vetek AB***

*Hantverksvägen 15 - 76493 Vaddö, Sweden*

*Tel +46-176208920 info@vetek.com*

**SALES AND TECHNICAL ASSISTANCE SERVICE**