


Datasheet 110ES-WL

Stainless Steel



Salt Waterproof Wireless Crane Scale IP68/69K

Shackles to be ordered separately.

DIMENSIONS

RATED CAPACITY	C	C 1	C 2	H	H 1	H 2	H 3	W	SUGGESTED SHACKLE
t/mm									
1	121	13	25	130.4	104	70	30.7	15.5	TBX-1.5t
2.5	121	15	25	130.4	104	70	30.7	17	TBX-2.5t
5	121	21	34	157.5	115.5	71.8	43.5	25	TBX-5t or RBXS-5t
10	133	31.5	50	197	141.5	72	63.3	40	TBX-12.5t
20	159	42	68	245	171	72.5	87	50	TBX-21t
30	205	45	80	295	206	92	99.5	52	TBX-30t
50	205	63	109	368	250	105	130	79	TBX-50t
100	273	90	152	496	332	146.5	174	112	TBX-110t

SPECIFICATIONS

Division	1t-10t: 1:5 000	Transmission Range	Up to 30m
	20t: 1:4 000	Operation Time	8 hours
	30t: 1:3 000	Rechargeable Battery Type	16340.3 7V x 4 (included)
	50t-100t: 1:5 000	Charger	DC 4.2V / 600mA (included)
Max. Safety Load	200% F.S.	Operating Temp.	-10°C to 40°C / 14°F to 104°F
Ultimate Load	400% F.S.	Operating Humidity	<85% RH under 20°C [68°F]
Enclosure	Stainless Steel Casting	IP Rating	IP68 / 69K

PART NUMBER

Rated Capacity	Frequency	Part No.	Self Weight (kg) (Batteries included)
1t	433 Mhz	110ES-1t-WL01	1.7
2.5t	433 Mhz	110ES-2.5t-WL01	1.7
5t	433 Mhz	110ES-5t-WL01	2.1
10t	433 Mhz	110ES-10t-WL01	3.5
20t	433 Mhz	110ES-20t-WL01	6.6
30t	433 Mhz	110ES-30t-WL01	10.5
50t	433 Mhz	110ES-50t-WL01	21
100t	433 Mhz	110ES-100t-WL01	53