

WWSB VEHICLE WEIGHING SYSTEMS

FEATURES

- Extended 17-key indicator keyboard
- LCD display with 6 25-mm high contrast digits and with indication of active functions, clearly visible even in poor lighting conditions and with low temperatures
- Rack type metallic case incl. housing for opt. printer
- Dimensions: 270 x 440 mm
- 4 fitted connectors (up to 8 optionally) for connection to 4 platforms
- 1 connector for connection to PC or radio modem
- Digital calibration and set-up from keyboard
- Instrument management and configuration from PC with DINITOOLS V.3


- Built-in rechargeable battery (10-hour min. operating time, recharge in 8 hrs) with fitted external 12 Vdc / 230 Vac adapter
- Std. connection with up to 4 WWS or TPS series' platforms
- Fitted with case with space for housing DFKW RACK indicator and space for housing other accessories
- Dimensions: 325x460x170 mm; Weight: about 5 kg

PLATFORM FEATURES

- Dimensions: 400 x 300 mm height 58 mm; weighs about 14,5 kg
- Cable, 10 m long, from platform to indicator
- Sturdy and handy structure, studied in each detail
- Easy to move around

SPECIFICATIONS

Code	Platform mm	Max Capacity	Division kg
WWSB600	400x300	600	0,2
WWSB1.5T	400x300	1500	0,5
WWSB3T	400x300	3000	1
WWSB6T	400x300	6000	2
WWSB8T	400x300	8000	5



DFKWR indicator Rack version including 4 connectors for link with the platforms, built-in rechargeable battery, case and battery charger.

IN THE WHEEL WEIGHING MODE WITH THE TOTAL FUNCTION IT IS POSSIBLE TO PRINT/DISPLAY:

- the weight of the single platforms
- the sum of any of their combinations
- the total weight of all the platforms (subtotals)

AFTER N WEIGHS IT IS POSSIBLE TO PRINT/DISPLAY:

- the number of weighs carried out, the accumulated weight and the sum of the subtotals carried out.

It is possible to carry out TARE operations and to know the barycentre and communicate the weight to PC.