

3590ET

3590ET "TOUCH": Touch Screen weight indicator for industrial applications



Digital weight indicator with a big touch screen display, suitable for advanced industrial applications. It allows the visualization of all the weighing data and the customization of the screens, simplifying the user operations. Fitted with 3 serial ports, transmission protocols for data communication, completely configurable printouts, integrated alibi memory, and port for connection to barcode/badge reader. CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:

VETEK WEIGHING AB

Hantverkarsvägen 15, 76493 Vaddö - Sweden
Tel: +46176-208920, info@vetek.com, www.vetek.com

**The best solution
for advanced industrial
applications**

MAIN FEATURES

- Backlit graphic display with touch screen technology, lxh= 120x90mm size. Screens completely customizable.
 - Multilanguage software.
 - QWERTY, AZERTY o QWERTZ keyboard, selectable.
 - ABS waterproof enclosure, with new IP65 protection system (IP40 on version with thermal printer).
 - Dimensions: 278x125x186 mm.
 - Suitable for use on the table, column, or wall.
 - Real time clock and permanent data storage.
 - Fitted alibi memory, integrated on the motherboard.
 - Slot for built-in micro SD for recording logos (upon request).
 - Functions available with DINI TOOLS utility
 - Configuration, data entry and print formatting.
 - Recording and filing of all the information on PC.
 - Complete retrieval of the configuration.
 - Instrument calibration with numeric values.
 - Customization of the screens.
 - 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
 - 4 independent analogue channels (up to 2 in the E-AF03 version) for reading of the weight.
 - Connection with up to 16 analogue load cells of 350 Ohm (45 load cells of 1000 Ohm) and with the main digital load cells available on the market (mod. E-AF03).
- Specific version available, which provides the management of the most common digital load cells for weigh bridges (models 3590ETD and 3590ETD8).
- Up to 10.000e OIML or 3 x 3000e @ 0,3 μ V/d CE-M legal for trade.
 - Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
 - Connectable to printers and labellers with free programming of the printout formats.
 - 110-240 Vac power supply.

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R51 - MID
- OIML R134 (AF09)

APPLICATION SOFTWARE

- AF01: Totalization and formula weighing (integrated)
- AF02: Pieces/quantity counting (optional)
- AF03: Weighbridges - Input/Output vehicle (optional)
- AF04: Statistical checking of prepackaged goods (optional)
- AF05: Price computing and industrial labelling (optional)
- AF08: Wheel and axle static weighing with 2 or various platforms (optional)
- AF09: Software for dynamic and static axle weighing with 1 or 2 platforms (optional)
- BATCH1: Single product dosage systems in loading and unloading (optional)

CUSTOMISED APPLICATIONS

Thanks to our integrated development, you can create complete customised applications in autonomy:

- wizards, operator messages
- serial port management, protocols customization
- digital I/O full management
- sequential or simultaneous automations
- data entry, custom archives

Dini Argeo can offer the service of custom development programs.

DETAIL 1



3590ETP



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne

DINI ARGEO
GMBH
Sinsheim - Germany

DINI ARGEO
UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO
WEIGHBRIDGES
Caltanissetta (CA) - Italy



HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano - Modena - Italy



VETEK WEIGHING AB

Hantverkarsvägen 15, 76493 Väddö - Sweden
Tel: +46176-208920, info@vetek.com, www.vetek.com

SALES AND TECHNICAL ASSISTANCE SERVICE