

# RL5426

RICE LAKE CANISTER LOAD CELL, IN STAINLESS STEEL, "RL5426" SERIES



Canister load cells for CE-M approved weighbridges, tanks, silos, etc. Manufactured in STAINLESS STEEL, IP69K protection degree, 6000 divisions.

---

**CAPACITIES:** 20 t, 30 t, 40t, 50 t.

---

**OIML R60. C6** precision class.

---

**Stainless steel** body. **IP69K** Protection Degree.

---

20 m Cable.

---

h= 118,5 mm.

---

Working in cooperation with:

**VETEK AB**

HANTVERKSVÄGEN 15 - 76493 - VÄDDÖ - SWEDEN  
Tel. +46176208920, info@vetek.com, www.vetek.com

The best solution  
for advanced industrial  
applications

## • TECHNICAL FEATURES

### METROLOGICAL FEATURES

- Rated capacity: (FS): 20t, 30t, 50t
- Combined error: 0,02 %F.S
- Creep error (after 30 min.): 0,02 %FS
- Temperature effect on zero: 0,003 %F.S./°C
- Temperature effect on sensitivity: 0,0008 %F.S./°C

### OIML R60

- $V_{min} = E_{max}/18000$
- Accuracy class: C6
- Max. number of intervals: 6000e OIML

### ELECTRONIC\MECHANICAL FEATURES



- Gas dischargers to protect against atmospheric discharges
- Power Supply: 5...15 Vdc
- Rated output at F.S.:  $2 \pm 0.1\%$  mV/V
- Input resistance:  $800 \pm 3\Omega$
- Output resistance:  $700 \pm 3\Omega$
- Insulation resistance: 5000M $\Omega$
- Operating temperature: -20 ~ +70 °C
- Compensated temperature for homologation: -10 ~ +40 °C
- Storage temperature limits: -40° ~ +80°
- Safe load limit: 120% F.S.
- Ultimate overload: 150% F.S.
- IP69K protection degree
- Stainless steel body
- 6-core cable, l= 20 m
- Nickel plated steel cable gland
- Self-centring spherical bases
- Equipped with anti-rotation system, to be combined with 173798 cups for proper operation

## CONNECTION

Cable Color Code	
RED	INPUT +
BLACK	INPUT -
GREEN	OUTPUT +
WHITE	OUTPUT -
YELLOW	SENSE +
BLUE	SENSE -
METAL	Shield

## VERSIONS

### Available versions

Codice	Max (kg)
177961 	20 000
177963 	30 000
177965 	40 000
177967 	50 000



[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano - Modena - Italy  
Tel. +39.0536 843418

**VETEK AB**

HANTVERKSVÄGEN 15 - 76493 - VÄDDÖ - SWEDEN

Tel. +46176-208920, [info@vetek.com](mailto:info@vetek.com), [www.vetek.com](http://www.vetek.com)

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.