

BLUETOOTH

BLUETOOTH INTERFACE FOR WEIGHT INDICATORS



Thanks to the Bluetooth <u>interface</u>, the exchange of data between the digital scales and the computer system will be simpler and quicker: it is sufficient to be at a few meters from the weight indicator in order to update the databases, read the memory, transmit commands, receive data, check the configuration, etc.

BLUETOOTH INTERFACE: FEATURES

• BLTH-2 MODEL:

- Standard: Bluetooth "version 3.0"

- Class: 2

- Identifying code of the programmable device

Maximum working distance: 10mTransmission speed: 560kbps

- Supported Bluetooth profiles: Serial Port Profile (SPP)

- Antenna: integrated on the board, internal

- Installation: integrated inside the weight indicator

NOTE: BLTH is an option to be specified when ordering the digital scale or the weight indicator.

SET OF COMMANDS AND COMMUNICATION PROTOCOLS

• The Dini Argeo weight indicators are fitted with a communication protocol for the data exchange, which allows the weight reading, the execution of the main scale functions and the programming of the databases (depending on the indicator model).

DETAIL 1



Evolved version for specific applications.





DINI ARGEO FRANCE sarl Nogent-sur-Marne info.fr@diniargeo.com DINI ARGEO GMBH Sinsheim - Germany info.de@diniargeo.com DINI ARGEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING INSTRUMENTS Ltd Shanghai - China info.cn@diniargeo.com

DINI ARGEO WEIGHBRIDGES Calto (RO) – Italy info@diniargeo.com









HEAD OFFICE

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418 Fax. +39.0536 843521 info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784 Fax. +39.0536 926654 service@diniargeo.com