

WIFITD

"WIFITD": WI-FI INTERFACE FOR INDICATORS



Small sized WIFI board for a connection inside the indicator with provided cable. The sticky antenna can be applied on the case and allows connecting any scale or weighing system to the corporate network.

Working in cooperation with:

VETEK AB

HANTVERKSVÄGEN 15 - 76493 - VÄDDÖ - SWEDEN
Tel. +46176-208920, info@vetek.com, www.vetek.com

The best solution
for advanced industrial
applications

TECHNICAL FEATURES

- Configuration through WIFI/Ethernet.
- Standard WiFi IEEE 802.11b/g/n device.
- Size: Height 17 mm, Width 50 mm, Length: 89 mm.
- Range: outdoor 70m, indoor 25m. Distance may change depending on the material of the indicator's case and on environment conditions.
- Frequency: 2.4/2.5 GHz.
- Data Rate: up to 500Kbps.
- Protocols and functioning modes: IEEE 802.11b/g/n, WEP, WPA and WPA2-PSK(AES/TKIP).
- Storage temperature: -40°C +95°C.
- Power supply: 5Vdc.

N.B. ACCESSORY WHICH MAY BE ORDERED ONLY COMBINED WITH A SUITABLE WEIGHT INDICATOR



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne

DINI ARGEO
GMBH
Sinsheim - Germany

DINI ARGEO
UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy



HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy



VETEK AB

HANTVERKSVÄGEN 15 - 76493 - VÄDDÖ - SWEDEN

Tel. +46176-208920, info@vetek.com, www.vetek.com

SALES AND TECHNICAL ASSISTANCE SERVICE